

Quadrangle Products Inc.

UL20276 10P+10C Shielded and Jacketed

SPECIFICATION		UL20276 30AWG/10P+30AWG/10C+AL/MY+DW+BRAID+JACKET		COLOR CODE
<b>ITEM</b>		<b>SPECIFICATION</b>		<b>30AWG/10P</b> 1. BLACK - BLACK/WHITE 2. BROWN - BROWN/WHITE 3. RED - RED/WHITE 4. ORANGE - ORANGE/WHITE 5. YELLOW - YELLOW/WHITE 6. GREEN - GREEN/WHITE 7. BLUE - BLUE/WHITE 8. PURPLE - PURPLE/WHITE 9. GRAY - GRAY/WHITE 10. PINK - PINK/WHITE
CONDUCTOR	AWG	30AWG/10P	30AWG/10C	
	MATERIAL	TINNED COPPER	TINNED COPPER	
	COND.SIZE	7/0.10mm	7/0.10mm	
<p align="center"><b>CROSS SECTION</b></p>				
<b>OUTER DIAMETER</b>		<b>5.80±0.20mm</b>		30AWG/10C: 1.BLACK 2.BROWN 3.RED 4.ORANGE 5.YELLOW 6.GREEN 7.BLUE 8.PURPLE 9.GRAY 10.WHITE
<b>ELECTRICAL CHARACTERISTICS</b>		<p align="center">Quadrangle Products Inc.</p>		<b>MARKING</b>
1.Rating: TEMP 80°C Rating voltage:30V 2.Conductor Resistance: AT 20°C MAX 30AWG:376.96Ω/KM				E238846  AWM 20276 80°C 30V VW-1