

Quadrangle Products Inc.

UL20276 17 PAIR Shielded and Jacketed

SPECIFICATION: 17P*28AWG+PAPER+Braid /UL20276		COLOR CODE	
ITEM	SPECIFICATION	1-Yellow & Yellow/Black 2- Red & Red/Black 3- Brown & Brown/White 4- Light Blue & Light Blue/Black 5-Light Blue/Green & Light Blue/Yellow 6- Green & Green/Black 7- Blue & Blue/White 8- White & White/Black 9- Pink & Pink/Black 10- Purple & Purple/White 11-Gray & Gray/Black 12-Orange & Orange/Black 13-Pink/White & Pink/Yellow 14- Gray/Green & Gray/Yellow 15- White/Yellow & White/Green 16- Light Green/Red & Green/Blue 17- Light Blue/Blue & Light Blue/Red	
CONDUCTOR	AWG		28AWG
	MATERIAL		TINNED COPPER
	COND.SIZE		7/0.127±0.008 mm
OUTER DIAMETER	7.00 +/- 0.15 mm		
ELECTRICAL CHARACTERISTICS		MARKING	
1. Rating : TEMP 80°C : VOLTAGE 30V 2. Conductor Resistance: AT 20°C MAX 28AWG: 237.25Ω/km;			
<p>Quadrangle Products Inc.</p>		E119932 AWM 20276 80°C 30V VW-1	