

# Quadrangle Products Inc.

# UL20276 25 PAIR Shielded and Jacketed

<b>SPECIFICATION:</b>		25P*28AWG +PAPER+Braid /UL20276	<b>COLOR CODE</b>
<b>ITEM</b>	<b>SPECIFICATION</b>		
<b>CONDUCTOR</b>	AWG	28AWG	1-Yellow & Yellow/Black
	MATERIAL	TINNED COPPER	2- Red & Red/Black
	COND.SIZE	7/0.127±0.008 mm	3- Brown & Brown/White
			4- Light Blue & Light Blue/Black
			5-Light Blue/Green & Light Blue/Yellow
			6- Green & Green/Black
			7- Blue & Blue/White
			8- White & White/Black
			9- Pink & Pink/Black
			10- Purple & Purple/White
			11- Gray & Gray/Black
			12- Orange & Orange/Black
			13- Pink/White & Pink/Yellow
			14- Gray/Green & Gray/Yellow
			15- White/Yellow & White/Green
			16- Light Green/Red & Green/Blue
			17- Light Blue/Blue & Light Blue/Red
			18- Pink/Red & Pink/Blue
			19- Gray/Red & Gray/Blue
			20-Green/White & Light Green/Blue
			21- Yellow/Red & Yellow/Green
			22- Red/White & Red/Blue
			23- White/Red & White/Blue
			24- Light Green & Light Green/Black
			25- Light Green/Yellow & Light Green/Green
<b>OUTER DIAMETER</b>		<b>8.30mm +/- 0.15 mm</b>	
<b>ELECTRICAL CHARACTERISTICS</b>			
1. Rating : TEMP 80°C : VOLTAGE 30V 2. Conductor Resistance: AT 20°C MAX 28AWG: 237.25Ω/km;			
			<b>MARKING</b>
Quadrangle Products Inc.			<b>E119932 UL AWM 20276 80°C 30V VW-1</b>