



Quadrangle Products Inc.

UL20276 5P+10C Shielded and Jacketed

SPECIFICATION		UL20276 30AWG/5P+30AWG/10C+AL/MY+DW+BRAID+JACKET		COLOR CODE
ITEM		SPECIFICATION		30 AWG/5P: 1. BLACK - BLACK/WHITE 2. BROWN - BROWN/WHITE 3. RED - RED/WHITE 4. ORANGE - ORANGE/WHITE 5. YELLOW - YELLOW/WHITE 30AWG/10C 1. BLACK 2. BROWN 3. RED 4. ORANGE 5. YELLOW 6. GREEN 7. BLUE 8. PURPLE 9. GRAY 10. WHITE
CONDUCTOR	AWG	30AWG/5P	30AWG/10C	
	MATERIAL	TINNED COPPER	TINNED COPPER	
	COND.SIZE	7/0.10mm	7/0.10mm	
<p style="text-align: center;">CROSS SECTION</p> <p style="text-align: center;"> Braiding UnitA (P1-P5) Shielding UnitB (1-10) Jacket </p>				
OUTER DIAMETER		5.10±0.20mm		
ELECTRICAL CHARACTERISTICS		 Quadrangle Products Inc.		MARKING
1. Rating TEMP: 80°C; Rating voltage: 30volts 2. Conductor Resistance: AT 20°C MAX 30AWG: 376.96Ω/KM				E238846  AWM 20276 80°C 30V VW-1