

<b>SPECIFICATION:</b> 10P*28AWG + PAPER +BRAID /UL20276		<b>COLOR CODE:</b>
<b>ITEM</b>	<b>SPECIFICATION</b>	<b>28 AWG/10P</b>
CONDUCTOR	28AWG	
MATERIAL	TINNED COPPER	
COND.SIZE	7/0.127±0.008 mm	
		<ol style="list-style-type: none"> <li>1. YELLOW - YELLOW/BLACK</li> <li>2. RED - RED/BLACK</li> <li>3. BROWN - BROWN/WHITE</li> <li>4. LIGHT BLUE - LIGHT BLUE/BLACK</li> <li>5. LIGHT BLUE/GREEN- LIGHT BLUE/YELLOW</li> <li>6. GREEN - GREEN/BLACK</li> <li>7. BLUE - BLUE/WHITE</li> <li>8. WHITE - WHITE/BLACK</li> <li>9. PINK - PINK/BLACK</li> <li>10. PURPLE - PURPLE/WHITE</li> </ol>
<b>OUTER DIAMETER</b>		6.00 ± 0.15 mm
<b>ELECTRICAL CHARACTERISTICS</b>		<p>Quadrangle Products Inc.</p>
1. Rating : TEMP 80°C ; VOLTAGE 30V 2. Conductor Resistance: at 20°C MAX 28AWG: 237.25Ω/km		
		<b>MARKING</b>
		MANUFACTURER# 91 AWM 20276 80°C 30V VW-1 (VARIOUS)

Quadrangle Products Inc.