

Quadrangle Products Inc.

UL20276 25 PAIR Shielded and Jacketed

SPECIFICATION:		25P*28AWG +PAPER+Braid /UL20276	COLOR CODE
CONDUCTOR	ITEM	SPECIFICATION	1-Yellow & Yellow/Black 2- Red & Red/Black 3- Brown & Brown/White 4- Light Blue & Light Blue/Black 5-Light Blue/Green & Light Blue/Yellow 6- Green & Green/Black 7- Blue & Blue/White 8- White & White/Black 9- Pink & Pink/Black 10- Purple & Purple/White 11- Gray & Gray/Black 12- Orange & Orange/Black 13- Pink/White & Pink/Yellow 14- Gray/Green & Gray/Yellow 15- White/Yellow & White/Green 16- Light Green/Red & Green/Blue 17- Light Blue/Blue & Light Blue/Red 18- Pink/Red & Pink/Blue 19- Gray/Red & Gray/Blue 20-Green/White & Light Green/Blue 21- Yellow/Red & Yellow/Green 22- Red/White & Red/Blue 23- White/Red & White/Blue 24- Light Green & Light Green/Black 25- Light Green/Yellow & Light Green/Green
	AWG	28AWG	
	MATERIAL	TINNED COPPER	
	COND.SIZE	7.0.127±0.008 mm	
OUTER DIAMETER		8.30mm +/- 0.15 mm	
ELECTRICAL CHARACTERISTICS		<p>Quadrangle Products Inc.</p>	
1. Rating : TEMP 80°C : VOLTAGE 30V 2. Conductor Resistance: AT 20°C MAX 28AWG: 237.25Ω/km;			
		MARKING MANUFACTURER# UL AWM 20276 80°C 30V VW-1 (VARIOUS)	