


TOLERANCE:

Abbr.	TOLERANCE				
	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54
P	± 0.05	± 0.08	± 0.08	± 0.10	± 0.20
Pt	± 0.08	± 0.10	± 0.10	± 0.15	± 0.2
W	± 0.12	± 0.15	± 0.15	± 0.20	± 0.2
M	± 0.08	± 0.12	± 0.12	± 0.20	± 0.30
Cw	± 0.02	± 0.03	± 0.03	± 0.03	± 0.04
L	(30~100) ± 3 , (101~300) ± 5 , (301~600) ± 10 , (Length more than 601mm) ± 15 mm				



Dimension	
Ft ± 0.01	0.043
St ± 0.01	0.223

Quadrangle P/N (Description)	No. of Conductor	Dimension										Support Tape Color	
		P	Pt	L	W	M	Cw	Ct ± 0.01	S1 ± 1.0	S2 ± 1.0	d1 ± 2.0		d2 ± 2.0
QDP0.50-40C0305BD-G	40	0.5	19.5	305	20.5	0.5	0.3	0.035	3	3	4	4	BLUE

UL Style

UL 20706 60 Volt; 105°C VW-1 RoHS Compliant

Marking

No

Conductor Material

GOLD

Units

mm



DWG BY: RJK	DATE: 12/5/2014	DRAWINGS ARE NOT TO SCALE. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. ALL TOLERANCES ARE +/- 0.50" UNLESS OTHERWISE SPECIFIED
CHK BY:	DATE:	
APPR:	DATE:	

REVISION HISTORY

REV	DATE	APPROVED
-----	INITIAL RELEASE	12/5/2014 RJK



Quadrangle Products Inc. 28 Harrison Ave Bldg 16D, Suite D, Englishtown, NJ 07726	Tel: 732-792-1234 Fax: 732-792-8305
---	--

© Copyright 2006 Quadrangle Products Inc. This document is confidential and proprietary to Quadrangle Products Inc. and shall not be reproduced, copied, used, or issued as the basis of manufacture or sale of equipment, material, or any other item. Quadrangle Products Inc. has the sole and exclusive ownership rights to this document and information contained herein.

QDP0.50-40C0305BD-G