

TOLERANCE:

Tolerance of Cutting Tilt

	Abbr.	TOLERANCE								
		P=0.5	P=0.8	P=1.0	P=1.25	P=2.54				
	P	±0.05	±0.08	±0.08	±0.10	±0.20				
	Pt	±0.08	±0.10	±0.10	±0.15	+0.2 -0.4				
	W	±0.12	±0.15	±0.15	±0.20	+0.2 -0.4				
	М	±0.08	±0.12	±0.12	±0.20	±0.30				
	Cw	±0.02	±0.03	±0.03	±0.03	±0.04				
		(30~100)±3, (101~300)±5, (301~600)±10,								

(Length more than 601mm)±15mm

Dimension					
Ft±0.01	0.043				
St±0.01	0.223				

Quadrangle P/N	No. of	Dimension						Support					
(Description)	Conductor	P	Pt	L	w	M	Cw	Ct±0.01	S1±1.0	S2±1.0	d1±2.0	d2±2.0	
QDP0.50-17C0051BD-TN	17	0.5	_8_	_51_	9	0.5	0.3	0.035	_4_	_4_	_8_	_8_	BLUE

UL Style

UL 20706 60 Volt; 105°C VW-1 RoHS Compliant

ARE IN INCHES UNLESS OTHERWISE SPECIFIED.

Marking No

Conductor Material

TIN

Units

mm

DATE: 5/24/19

DWG BY: PT



			ARE IN INCHES UNLESS OTHERWISE SPECI					
CHK BY:		DATE:		NLESS OTHERWISE SPECIFIED. NCES ARE +/- 0.50" UNLESS				
APPR:		DATE:	OTHE	ΞD				
		REVIS	ION HISTORY					
REV	REV			DATE	APPROVED			
		Drawing Upda	te	5/24/2019	PT			



Quadrangle Products Inc. 28 Harrison Ave Suite 241 Englishtown, NJ 07726

Tel: 732-792-1234 Fax: 732-792-8305

© Copyright 2006 Quadrangle Products Inc. This document is confidential and proprietary to Quadrangle Products Inc. and shall not be reproduced, copied, used, or issued as the basis of manufacture or sale of equipment, material, or any other item. Quadrangle Products Inc. has the sole and exclusive ownership rights to this document and information contained herein.

QDP0.50-17C0051BD-TN