


**TOLERANCE:**

Abbr.	TOLERANCE				
	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54
P	±0.05	±0.08	±0.08	±0.10	±0.20
Pt	±0.08	±0.10	±0.10	±0.15	±0.2
W	±0.12	±0.15	±0.15	±0.20	±0.4
M	±0.08	±0.12	±0.12	±0.20	±0.30
Cw	±0.02	±0.03	±0.03	±0.03	±0.04
L	(30~100)±3, (101~300)±5, (301~600)±10, (Length more than 601mm)±15mm				



Tolerance of Cutting Tilt

Dimension	
Ft±0.01	0.043
St±0.01	0.223

Quadrangle P/N (Description)	No. of Conductor	Dimension										Support Tape Color	
		P	Pt	L	W	M	Cw	Ct±0.01	S1±1.0	S2±1.0	d1±2.0		d2±2.0
<b>QDP0.50-32C0256AD-T</b>	32	0.5	15.5	256	16.5	0.5	0.3	0.035	4	4	8	8	BLUE

**UL Style**

UL 20706 60 Volt; 105°C VW-1 RoHS Compliant

**Marking**

No

**Conductor Material**

TIN

**Units**

mm



DWG BY: PT	DATE: 5/20/19
CHK BY:	DATE:
APPR:	DATE:

DRAWINGS ARE NOT TO SCALE. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. ALL TOLERANCES ARE +/- 0.50" UNLESS OTHERWISE SPECIFIED

**REVISION HISTORY**

REV		DATE	APPROVED
-----	Created new drawing	5/20/2019	PT
-----			
-----			
-----			



Quadrangle Products Inc.  
28 Harrison Ave Suite 105,  
Englishtown, NJ 07726

Tel: 732-792-1234  
Fax: 732-792-8305

© Copyright 2006 Quadrangle Products Inc. This document is confidential and proprietary to Quadrangle Products Inc. and shall not be reproduced, copied, used, or issued as the basis of manufacture or sale of equipment, material, or any other item. Quadrangle Products Inc. has the sole and exclusive ownership rights to this document and information contained herein.

**QDP0.50-32C0256AD-T**