


TOLERANCE:

Abbr.	TOLERANCE				
	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54
P	±0.05	±0.08	±0.08	±0.10	±0.20
Pt	±0.08	±0.10	±0.10	±0.15	±0.2
W	±0.12	±0.15	±0.15	±0.20	±0.2
M	±0.08	±0.12	±0.12	±0.20	±0.30
Cw	±0.02	±0.03	±0.03	±0.03	±0.04
L	(30~100)±3, (101~300)±5, (301~600)±10, (Length more than 601mm)±15mm				



Dimension	
Ft±0.01	0.043
St±0.01	0.223

Quadrangle P/N (Description)	No. of Conductor	Dimension											Support Tape Color
		P	Pt	L	W	M	Cw	Ct±0.01	S1±1.0	S2±1.0	d1±2.0	d2±2.0	
QDP1.00-18C0381BD-T	18	1.00	17	381	19	1.00	0.65	0.035	6	6	10	10	BLUE

UL Style

SUMITOMO-Y AWM 2896 80C VW-1

Marking

YES

Conductor Material

TIN

Units

mm



DWG BY: PT	DATE: 8/6/19	DRAWINGS ARE NOT TO SCALE. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. ALL TOLERANCES ARE +/- 0.50" UNLESS OTHERWISE SPECIFIED
CHK BY:	DATE:	
APPR:	DATE:	

REVISION HISTORY

REV		DATE	APPROVED
-----	New Drawing	8/6/2019	PT



Quadrangle Products Inc.

Quadrangle Products Inc.
28 Harrison Ave Suite 105
Englishtown, NJ 07726

Tel: 732-792-1234
Fax: 732-792-8305

© Copyright 2006 Quadrangle Products Inc.
This document is confidential and proprietary to Quadrangle
Products Inc. and shall not be reproduced, copied, used, or
issued as the basis of manufacture or sale of equipment,
material, or any other item. Quadrangle Products Inc. has the
sole and exclusive ownership rights to this document and
information contained herein.

**QDP1.00-
18C0381BD-T**