


TOLERANCE:

Abbr.	TOLERANCE				
	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54
P	±0.05	±0.08	±0.08	±0.10	±0.20
Pt	±0.08	±0.10	±0.10	±0.15	± 0.2 ± 0.4
W	±0.12	±0.15	±0.15	±0.20	± 0.2 ± 0.4
M	±0.08	±0.12	±0.12	±0.20	±0.30
Cw	±0.02	±0.03	±0.03	±0.03	±0.04
L	(30~100)±3, (101~300)±5, (301~600)±10, (Length more than 601mm)±15mm				

Dimension	
Ft±0.01	0.043
St±0.01	0.223



Quadrangle P/N (Description)	No. of Conductor	Dimension										Support Tape Color	
		P	Pt	L	W	M	Cw	Ct±0.01	S1±1.0	S2±1.0	d1±2.0		d2±2.0
QDP1.00-22C0305BD-T	<u>22</u>	<u>1.00</u>	<u>21</u>	<u>305</u>	<u>23</u>	<u>1.00</u>	<u>0.65</u>	<u>0.035</u>	<u>4</u>	<u>4</u>	<u>8</u>	<u>8</u>	<u>BLUE</u>

UL Style
SUMITOMO-Y- AWM UL2896 80C VW-1- **Marking**
YES

Conductor Material
TIN

Units
mm



DWG BY: PT DATE: 8/9/19 DRAWINGS ARE NOT TO SCALE. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. ALL TOLERANCES ARE +/- 0.50" UNLESS OTHERWISE SPECIFIED

REVISION HISTORY			
REV	DATE	APPROVED	
-----	New Drawing	8/9/2019	PT



Quadrangle Products Inc.
28 Harrison Ave Suite 105
Englishtown, NJ 07726

Tel: 732-792-1234
Fax: 732-792-8305

© Copyright 2006 Quadrangle Products Inc. This document is confidential and proprietary to Quadrangle Products Inc. and shall not be reproduced, copied, used, or issued as the basis of manufacture or sale of equipment, material, or any other item. Quadrangle Products Inc. has the sole and exclusive ownership rights to this document and information contained herein.

QDP1.00-22C0305BD-T