

Conductor

## TOLERANCE:

Tolerance of Cutting Tilt

Abbr.	TOLERANCE								
ADDr.	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54				
Р	±0.05	±0.08	±0.08	±0.10	±0.20				
Pt	±0.08	±0.10	±0.10	±0.15	+0.2 -0.4				
₩	±0.12	±0.15	±0.15	±0.20	+0.2 -0.4				
М	±0.08	±0.12	±0.12	±0.20	±0.30				
Cw	±0.02	±0.03	±0.03	±0.03	±0.04				

(30~100)±3, (101~300)±5, (301~600)±10, (Length more than 601mm)±15mm

Dir	nension
Ft±0.01	0.043
St±0.01	0.223

Quadrangle P/N	No. of	Dimension					Support						
(Description)	Conductor	P	Pt	L	w	M	Cw	Ct±0.01	S1±1.0	S2±1.0	d1±2.0	d2±2.0	Tape Color
QDP1.25-08C0051BD-T	8	1.25	8.75	_51_	<u>11.2</u> 5	1.25	0.8	0.035	_5_	_5_	10_	_10_	BLUE

**UL Style** 

UL 20706 60 Volt; 105°C VW-1 RoHS Compliant

Marking

Nο

## **Conductor Material**

TIN

Units

mm



DWG BY: PT		DATE:8/22/19	DRAWINGS ARE NO				
CHK BY:		DATE:	ARE IN INCHES UNLESS OTHERWISE SPECIFIE ALL TOLERANCES ARE +/- 0.50" UNLESS				
APPR:		DATE:	OTHERWISE SPECIFIED				
	REVISION HISTORY						
REV				DATE	APPROVED		
		New Drawing	1	8/22/2019	PT		

Quadrangle Products Inc. 28 Harrison Ave Suite 105 Englishtown, NJ 07726

Tel: 732-792-1234 Fax: 732-792-8305

© Copyright 2006 Quadrangle Products Inc. This document is confidential and proprietary to Quadrangle Products Inc. and shall not be reproduced, copied, used, or issued as the basis of manufacture or sale of equipment, material, or any other item. Quadrangle Products Inc. has the sole and exclusive ownership rights to this document and information contained herein.

QDP1.25-08C0051BD-T