



TOLERANCE:

Abbr.	TOLERANCE				
	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54
P	±0.05	±0.08	±0.08	±0.10	±0.20
Pt	±0.08	±0.10	±0.10	±0.15	±0.20
W	±0.08	±0.10	±0.10	±0.20	±0.20
M	±0.08	±0.12	±0.12	±0.20	±0.30
Cw	±0.02	±0.03	±0.03	±0.03	±0.04
L	(30~100)±3, (101~300)±5, (301~600)±10, (Length more than 601mm)±15mm				

Dimension	
Ft±0.01	0.043
St±0.01	0.223

Quadrangle P/N (Description)	No. of Conductor	Dimension										Support Tape Color	
		P	Pt	L	W	M	Cw	Ct±0.01	S1±1.0	S2±1.0	d1±2.0		d2±2.0
QDP1.25-15C0237BD-TN	15	1.25	17.5	237	20	1.25	0.8	0.035	6	6	8	8	BLUE

UL Style

E229188 AWM UL2896 80C 30V VW-1

Marking

Yes

Conductor Material

TIN

Units

mm



DWG BY: MHB
 CHK BY:
 APPR:

DATE: 7/15/2009
 DATE:
 DATE:

DRAWINGS ARE NOT TO SCALE. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. ALL TOLERANCES ARE +/- 0.50" UNLESS OTHERWISE SPECIFIED

REVISION HISTORY

REV	DATE	APPROVED
-----	INITIAL RELEASE	7/15/2009 MHB



Quadrangle Products Inc.
 28 Harrison Ave Suite 105
 Englishtown, NJ 07726

Tel: 732-792-1234
 Fax: 732-792-8305

© Copyright 2006 Quadrangle Products Inc. This document is confidential and proprietary to Quadrangle Products Inc. and shall not be reproduced, copied, used, or issued as the basis of manufacture or sale of equipment, material, or any other item. Quadrangle Products Inc. has the sole and exclusive ownership rights to this document and information contained herein.

QDP1.25-15C0237BD-TN