


TOLERANCE:

Abbr.	TOLERANCE								
Abbr.	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54				
Р	±0.05	±0.08	±0.08	±0.10	±0.20				
Pt	±0.08	±0.10	±0.10	±0.15	+0.2 -0.4				
W	±0.12	±0.15	±0.15	±0.20	+0.2 -0.4				
М	±0.08	±0.12	±0.12	±0.20	±0.30				
Cw	±0.02	±0.02 ±0.03		±0.03	±0.04				

(30~100)±3, (101~300)±5, (301~600)±10, (Length more than 601mm)±15mm



Dimension				
Ft±0.01	0.043			
St±0.01	0.223			

Quadrangle P/N	No. of	No. of Dimension					Support						
(Description)	Conductor	P	Pt	L	w	M	Cw	Ct±0.01	S1±1.0	S2±1.0	d1±2.0	d2±2.0	Tape Color
QDP1.25-20C0305BD-T	20	1.25	23.75	305	26.25	1.25	0.8	0.035	_4_	_4_	_8_	_8_	BLUE

Marking **UL Style** E229188 AWM UL2896 80C 30V VW-1 Yes

Conductor Material

TIN

Units

mm



DWG	BY: PT	DATE:8/15/19	DRAWINGS ARE NO	OT TO SCALE	ALL DIMENSIONS		
DWG BT. FT		DATE:0/10/10	ARE IN INCHES UN				
CHK BY:		DATE:	ALL TOLERAN				
APPF	₹:	DATE:	OTHERWISE SPECIFIED				
REVISION HISTORY							
REV				DATE	APPROVED		
	New Drawing			8/15/2019	PT		

REVISION HISTORY						
REV		DATE	APPROVED			
	New Drawing	8/15/2019	PT			



Quadrangle Products Inc. 28 Harrison Ave Suite 105 Englishtown, NJ 07726

Tel: 732-792-1234 Fax: 732-792-8305

© Copyright 2006 Quadrangle Products Inc. This document is confidential and proprietary to Quadrangle Products Inc. and shall not be reproduced, copied, used, or issued as the basis of manufacture or sale of equipment, material, or any other item. Quadrangle Products Inc. has the sole and exclusive ownership rights to this document and information contained herein.

QDP1.25-20C0305BD-T