


TOLERANCE:

Abbr.	TOLERANCE				
	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54
P	±0.05	±0.08	±0.08	±0.10	±0.20
Pt	±0.08	±0.10	±0.10	±0.15	± 0.2 -0.4
W	±0.12	±0.15	±0.15	±0.20	± 0.2 -0.4
M	±0.08	±0.12	±0.12	±0.20	±0.30
Cw	±0.02	±0.03	±0.03	±0.03	±0.04
L	(30~100)±3, (101~300)±5, (301~600)±10, (Length more than 601mm)±15mm				

Dimension	
Ft±0.01	0.043
St±0.01	0.223



Quadrangle P/N (Description)	No. of Conductor	Dimension											Support Tape Color
		P	Pt	L	W	M	Cw	Ct±0.01	S1±1.0	S2±1.0	d1±2.0	d2±2.0	
QDP0.50-18C0076BD-T	18	0.5	8.5	76	9.5	0.5	0.3	0.035	4	4	8	8	BLUE

UL 20706 60 Volt; 105°C VW-1 RoHS Compliant

Units: mm

DWG BY: PT
 CHK BY:
 APPR:

DATE: 3/18/21
 DATE:
 DATE:

DRAWINGS ARE NOT TO SCALE. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. ALL TOLERANCES ARE +/- 0.50" UNLESS OTHERWISE SPECIFIED



Quadrangle Products Inc.
 28 Harrison Ave Suite 105,
 Englishtown, NJ 07726

Tel: 732-792-1234
 Fax: 732-792-8305

© Copyright 2006 Quadrangle Products Inc. This document is confidential and proprietary to Quadrangle Products Inc. and shall not be reproduced, copied, used, or issued as the basis of manufacture or sale of equipment, material, or any other item. Quadrangle Products Inc. has the sole and exclusive ownership rights to this document and information contained herein.

QDP0.50-18C0076BD-T

REVISION HISTORY			
REV		DATE	APPROVED
-----	INITIAL RELEASE	3/18/2021	PT

